

# ASPECT® 300

## The TIG AC/DC new aspect!

ASPECT® 300 is an industrial AC/DC TIG welding machine designed and manufactured using the latest inverter digital technology. This machine has been designed and built to perform in the most hazardous environments at high outputs: 300A at 35% duty cycle both in TIG AC and TIG DC application. The controller provides all the features you would expect from industrial AC/DC TIG inverter welding machines combined with a user-friendly front panel layout, setting advanced TIG parameters has never been so simple!

The top class features like the 2A minimum current, the multiple AC mode selection (including four different wave shapes), the optimized TIG start with adjustable electrode type and HF polarity, makes the unit the right choice to suit any application.

It can be simply changed to water-cooled by adding the COOL ARC® 46 Water Cooler. A robust, stable and well equipped cart is available for easy movement of the unit.

### Features

- Advanced inverter technology for superior TIG performance.
- Superb welding characteristics with TIG DC, TIG AC and Stick welding processes.
- Adjustable cleaning and penetration for perfect aluminium welding.
- Variable AC frequency (40-400Hz) for control of travel speed and penetration.
- Full function user-friendly control panel layout with graph and a numeric display make it easy to set all welding parameters.
- Rugged construction: electrical safety (IP23), potted PC boards and optimum airflow reduce contamination to extend the equipment's life in the harshest environmental conditions.
- PFC (Power Factor Correction) advantages: 30% more output current with the same input current, suitable for 230-400V (+15%-10%) three phase, low current consumption, energy saving, low current harmonics and reduction of the total CO<sub>2</sub> produced by the welding process.
- Water coolers and Carts available.



#### Processes

- Stick DC, Stick AC
- TIG DC, TIG AC
- Lift TIG, TIG HF
- TIG Pulse



#### Recommended Consumables

- **Steel**  
LNT 25, LNT 26, LNT Ni1, LNT 19
- **Stainless steel**  
LNT 304L, 316L, 309L
- **Aluminium**  
SuperGlaze®

#### Unit Includes

- 3m input cable
- Gas connection kit

#### Key Options

- **KIT-300A-50-xM** Cable Kit 300A - 50 mm<sup>2</sup> - 5/10m
- **E/H-300A-50-xM** Electrode holder 300A - 50 mm<sup>2</sup> - 5/10m
- **GRD-300A-50-xM** Ground cable 300A - 50 mm<sup>2</sup> - 5/10 m
- **K10513-26-x** TIG torch LT 26 G - 180A - 4/8 m
- **K10513-18-x** TIG torch LT 18 W - 320A - 4/8 m
- **K10513-185C-x** Tig Torch LT 185C W - 400A - 4/8 m
- **KP10516-11** Accessory kit LT17/18/26 - 1,6 - 2,4mm
- **KP10516-12** Accessory kit LT17/18/26 - 2,4 - 3,2mm.
- **K870** Foot Amptrol
- **K14147-1** Remote control - 15 m
- **K14148-1** Extension for remote control 15m
- **K14105-1** Water cooler COOL ARC® 46
- **K10420-1** Coolant Acorox (2x5l)
- **K14129-1** Cart TPX



#### INPUT



#### OUTPUT



### Technical Specifications

Product	Item Number	Primary Voltage (50-60Hz)	Current Range (A)	Rated Output	Fuse Size (A) (slow)	Weight (kg)	Dimensions HxWxD (mm)	Protection/Insulation Class
ASPECT® 300	K12058-1	230/400V/3Ph	2 - 300	300A/22V/35% 200A/18V/100%	32/20	43	455 x 301 x 632	IP23 / H

