

XTE 181C Automotive Compact Mig Machine



AUTOMOTIVE MIG MACHINES



- 230V Single Phase
- 180A @ 20% Duty Cycle
- 2 Roll Drive and holds 15kg Wire Spools
- Forced Air Fan Cooling
- Infinitely Variable Wire Speed
- Built in Gas Valve
- Overload Warning Indicator
- Stand for Half Size Gas Cylinder
- Supplied with Regulator and Torch
- 2 Years Return to Base Warranty
- Manufactured to IP23S, EN/IEC 60974-1 RoHS Directive, Low Voltage Directive and EMC Directive (CE Compliant)



SINGLE PHASE COMPACT MIG MACHINE SUPPLIED WITH BUILT IN WIRE FEEDER

Standard Package Includes

| STOCK CODE | DESCRIPTION |
|--------------|--------------------------------------|
| XTMCA | Input Cable x 4m |
| XTMGH3 | Gas Hose x 3m 3/8" BSP Fittings |
| ECR1500-30ER | Eco-Grip Max® MIG Torch Package x 3m |
| E700123 | Regulator 300 Bar SS 2G Argon |

| STOCK CODE | DESCRIPTION |
|------------|--|
| XTE181 | 180A Automotive MIG Machine 230V |
| XTE181-P1 | Automotive MIG Machine complete with Torch and Regulator |

Accessories

| STOCK CODE | DESCRIPTION |
|------------|----------------------------------|
| 706101 | Flow Meter Mixed Gas 25lpm (MIG) |
| 806001 | Gas Flow Tester |

DC Output

The XTE 181C has a DC Output and when combined with the correct type of wire it is suitable for welding mild steel, stainless steel and aluminium from 0.75mm to 5.0mm.

Reliable Feeding

The geared aluminium feed box ensures reliable feeding of 0.8mm and 1.0mm wires.

Versatile and Portable

The XTE 181C full size cabinet can accept a gas cylinder and its large wheels mean it is easily portable and can be moved from job to job.

| STOCK CODE | DESCRIPTION |
|------------|-------------------------|
| CERT-MIG | Calibration Certificate |

Calibration Certificates are available at the time of order (please note that this is an additional cost).

WARRANTY VALID FOR UK AND EIRE ONLY

Technical Information

| PARAMETER | VALUE |
|----------------------|-----------------|
| Cabinet Format | Compact |
| Machine Type | Transformer |
| Current Range | 35-180A |
| Input Voltage | 230V 1P |
| Minimum fuse size | 20A |
| Voltage Steps | 6 |
| Duty Cycle | 180A @ 20% |
| Spool Size | 300 |
| Wire Sizes | 0.6-1.0mm |
| Fuse Rating | 32A |
| KVA | 9.8 |
| Enclosure Protection | IP23S |
| Dimensions (mm) | 845 x 415 x 505 |
| Weight (kg) | 55 |



FIND MORE INFORMATION ON OUR YOUTUBE CHANNEL, PARWELDTV



Sales: +44 (0) 1299 266800
E-Mail: info@parweld.co.uk

