

# XTM 200I MIG Inverter



## LIGHTWEIGHT PORTABLE MIG INVERTER MACHINE

### DC Output

The smooth DC output ensures excellent arc characteristics. Materials up to 4mm can be welded with ease. The arc voltage is infinitely adjustable providing exact settings of the welding parameters. Lightweight construction means the machine is very portable and the removable euro connection torch makes for easy transport and storage.

The dual digital displays allow all the welding parameters to be displayed, welding voltage is displayed constantly and the second display can be toggled between the wire speed and welding amperage.

Wire sizes of 0.6-1.0mm can be used with ease.

### Generator Friendly

The XTM 200I is able to cope with inputs which fluctuate by +/- 15% and can be used with the majority of generators.

The machine is housed in a steel case with an integrated carry handle and shoulder strap

STOCK CODE	DESCRIPTION
XTM200I	200A MIG Inverter
XTM200I-P1	MIG Inverter with MIG Torch & Regulator

### Accessory Information

STOCK CODE	DESCRIPTION
CKC403	Earth Cables Clamp Kit x 3m
ECR1500-30ER	Eco-Grip Max® 150A MIG Torch x 3m
PRO1500-30ER	Pro-Grip Max® 150A MIG Torch x 3m
E700123	Argon Regulator Single Stage 2 Gauge
XR935H	Everyday Light Reactive Helmet – Black
WP17V-12-2I	WP17V Torch Package x 12.5ft
XR935H	Everyday Light Reactive Helmet – Black

WARRANTY VALID FOR UK AND EIRE ONLY

Sales: +44 (0) 1299 266800  
E-Mail: [info@parweld.co.uk](mailto:info@parweld.co.uk)

- 230V Single Phase
- 200A @ 20% Duty Cycle
- Compact and Portable
- Dual Digital display
- Accepts 5kg (200mm) Spools
- IP23S
- Supplied with Regulator and MIG Torch
- 2T/4T trigger latching
- Synergic Control Trolley with Built in Storage Drawer
- 3 Years Return to Base Warranty
- Manufactured to IP23S, ISO/IEC 60974-1, ISO/IEC 60974-6 and RoHS Compliant

### Technical Information

PARAMETER	VALUE
Style	Portable
Machine Type	Inverter
Maximum Current	200A
Wire Feed Speed	2-18m/min
Voltage	16-22V
Spool Size	200mm
Feed Box	2R
Wire Size	0.8-1.0mm
Duty Cycle	200A @ 30%
Input Voltage	230V 1P
Input Current (Max)	40A
Minimum Fuse Rating	16A
KVA	5.4
Enclosure Protection	IP23S
Dimensions (mm)	465 x 214 x 356
Weight (kg)	12

FOR MORE INFORMATION ON OUR PRO-GRIP MAX® 150A\* BZL TORCH GO TO PAGE 51



\* Image may differ from torch



parweld  
WELDING THE FUTURE

MIG INVERTER MACHINES