# XTT 182DV TIG Inverter





## PROFESSIONAL LEVEL DUAL VOLTAGE DC TIG INVERTER

#### DC Output

The XTT 182DV has a DC output and is suitable for welding alloy, non alloy steels, stainless steel and titanium. TIG Mode - Materials up to 6mm can be welded with ease. MMA Mode - Electrodes up to 4.8mm can be used with ease.

#### TIG Welding

The XTT 182DV can be used for TIG welding and is suitable for welding steel and stainless steel using the HF start circuit. The latching trigger function improves operator comfort allowing the trigger to be released during Long welds.

### Generator Friendly

The XTT 182DV is able to cope with inputs which fluctuate by +/-15% and can be used with the majority of generators. The machine is housed in a metal case with integrated carry handle and shoulder strap.

A carry case is available as an optional extra.

STOCK CODE	DESCRIPTION
XTT182DV	180A DC Tig Inverter 110/230V
XTT182DV-P1	TIG Inverter and PRO26 TIG Torch Package and Regulator

### Accessory Information

STOCK CODE	DESCRIPTION
CKE403	Electrode Holder Cable Kit x 3m
CKC403	Earth Cables Clamp Kit x 3m
PRO26-12SIBD19	Pro-Grip Max® TIG 200A Air Cooled Torch 12.5ft
ERCP19	5 Pin XTI Inverter Plug
D3595-1-1	TIG Adaptor
E700123	Argon Regulator Single Stage 2 Gauge
WP26AK	TIG Spares Kit in Plastic Case
XTI903T	Foot Control
XR935H	Everyday Light Reactive Welding Helmet
XTICL	Large Carry Case (Sold separately)

WARRANTY VALID FOR UK AND EIRE ONLY





#### Dual Voltage 110/230V

- Lightweight 7.8kg
- 180A @ 60% Duty Cycle
- Generator Friendly
- Easy Electrode Re-striking with Hot Start (MMA)
- HF Arc Starting
- Adjustable Post Flow (TIG Mode)
- Supplied with 3m Earth Lead
- Latching Trigger Option (TIG Mode)
- Adjustable Downslope (TIG Mode)
- Connections 35-50mm Dinse
- 3 Years Return to Base Warranty
- Manufactured to IP23S, ISO/IEC 60974-1, ISO/IEC 60974-6 and RoHS Compliant

# Technical Information

A 0V 1P
х. Х
060%
30 x 240
1



## Sales: +44 (0) 1299 266800 E-Mail: info@parweld.co.uk